



COLARUS GROUP

+1-877-359-1257 (Toll Free)

+1-238-938-1727

+1-905-594-1727


Elbow 90

Malleable Black Iron



In a Black Iron Pipe Elbow Piping System, the elbow is a pipe fitting that changes the direction of the pipeline at a 90-degree bend.

Standard:	EN10242 / ANSI / ASME B16.3 / DIN2950 / ISO49 / NBR6943 / Is1879 / EN10242
Thread Standard:	EN10226 / ASME B1.20.1 / DIN 2999 ISO-1 / ISO228 / IS 554 / BS EN10226
Working Pressure	PN 25 / 2.5 MPA / CLASS 150 / 25 BAR



Product Code	Product Description	Size	DN	A	Weight	PSI
		(ANSI)	(mm)	(mm)	(g)	
ELB90-18-MBK	Elbow 90- 1/8" Malleable Black Iron	1/8"	6	18	30.38	150
ELB90-14-MBK	Elbow 90- 1/4" Malleable Black Iron	1/4"	8	20	42.14	150
ELB90-38-MBK	Elbow 90- 3/8" Malleable Black Iron	3/8"	10	24	60.76	150
ELB90-12-MBK	Elbow 90- 1/2" Malleable Black Iron	1/2"	15	27	96.04	150
ELB90-34-MBK	Elbow 90- 3/4" Malleable Black Iron	3/4"	20	32	139.16	150
ELB90-1-MBK	Elbow 90- 1" Malleable Black Iron	1"	25	37	213.64	150
ELB90-114-MBK	Elbow 90- 1-1/4" Malleable Black Iron	1-1/4"	32	44.5	340.06	150
ELB90-112-MBK	Elbow 90- 1-1/2" Malleable Black Iron	1-1/2"	40	48.5	423.36	150
ELB90-2-MBK	Elbow 90- 2" Malleable Black Iron	2"	50	57	674.24	150

Working Pressure : 25BAR / 363PSI / MPA / CLASS / PN 25
Temperature : 200 °c (392°F)
Tensile Strength : ≥350MPA
Elongation : ≥10%
Hardness : ≤HB150



3588 Grassie Road, Grassie.
 ON, Canada. L0R 1M0
 E-mail: sales@colarusgroup.ca
 E-mail: colarusgroup@gmail.com

